

# J O S E P H H A M I L T O N & S E A T O N



## MAINSTAY

Construction	Loop Pile Tile
Pile Content	100% Polypropylene
Primary Backing	Non Woven Polypropylene
Secondary Backing	Modified Bitumen with reinforcing glass fibre
Tile Size	50cm x 50cm
Pile Weight	580gms
Total Weight	4,100gms
Pile Height	3.4mm
Total Height	6.2mm
Box No	20 tiles per box
Gauge	1/10 <sup>th</sup>

Antistatic	<2kv
Impact Sound Insulation	39db (ISO 10140)
Sound Absorption	0.19 at 1,000 Hz (ISO 354)
Tog Rating	0.45 Max temp for under floor heating 30°c
Thermal Retention	0.045m <sup>2</sup> /kw (ISO 8302)
Permanent Antistatic	=<2kv (ISO 6356)
Castor Chair	B (occasional use) EN 985
Light Fastness	5-6 (ISO-B02)
Water Fastness	>=4 (ISO- E01)
Dry Rubbing	>=4 (ISO 105-x12)
VOC	22555
Flammability	BS 4790 (Hot Metal Nut Test) Low radius of ignition EN 13501-1 – CfIS1

Guarantees: 5 years heavy commercial  
5 year anti-shock  
Full details of conditions and limits of guarantees available on request.



2009/533

**JOSEPH HAMILTON & SEATON**  
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401  
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152